


MHS-LSZH

Halogen free indoor cable



APPLICATION Indoor cable for access networks

CONSTRUCTION	Conductor	Annealed, tinned copper wire
	Insulation	Solid PE
	Twinning	Two insulated conductors in a pair
	Lay-up	Stranded into units
	Ground wire	Annealed, tinned copper wire
	Screen	Plastic-aluminium foil
	Sheath	Grey HFFR-compound

SSTL code	Type MHS-LSZH	Draka code	Diameter mm	Sheath thickness mm	Mass kg/km	Delivery length m	Drum/ packaging
0202402	1x4x0.5	1003590	5.1	1.0	28	1000	K5
0202404	1x4x0.5	1003590-00100RW	5.1	1.0	28	100	coil
0202406	1x4x0.5	1003590-00300RW	5.1	1.0	28	300	coil
0202408	3x2x0.5	1003591	5.8	1.0	36	1000	K6
0202410	3x2x0.5	1003591-00200RW	5.8	1.0	36	200	coil
0202412	5x2x0.5	1003592	6.7	1.0	49	1000	K6
0202414	5x2x0.5	1003592-00150RW	6.7	1.0	49	150	coil
0202416	10x2x0.5	1004746-01000DX	7.8	1.0	73	1000	K6
0202418	10x2x0.5	1004746-00200RW	7.8	1.0	73	200	coil
0202420	20x2x0.5	1004749-01000DW	9.2	1.0	120	1000	K7
0202422	20x2x0.5	1004749-00150RS	9.2	1.0	120	150	coil
0202424	30x2x0.5	1004751-01000DX	11.0	1.1	170	1000	K8
0202426	50x2x0.5	1004753-01000DX	14.0	1.1	270	1000	K9
0202428	100x2x0.5	1004745-01000DX	19.5	1.2	505	1000	K12