


MHS

Indoor cable



APPLICATION	Indoor cable for access networks	
CONSTRUCTION	Conductor	Annealed, tinned copper wire
	Insulation	Solid PE
	Twinning	Two insulated conductors in a pair
	Lay-up	Stranded into units
	Ground wire	Annealed, tinned copper wire
	Screen	Plastic-aluminium foil
	Sheath	Grey PVC

SSTL code	Type MHS	Draka code	Diameter mm	Sheath thickness mm	Mass kg/km	Delivery length m	Drum/ packaging
0295131	1x4x0.5	1003545-01000DO	4.5	1.0	30	1000	K5
0255121	1x4x0.5	1003545-00100RW	4.5	1.0	30	100	coil
0255131	1x4x0.5	1003545-00300RW	4.5	1.0	30	300	coil
0295132	3x2x0.5	1003542-01000DO	5.0	1.0	36	1000	K6
0255132	3x2x0.5	1003542-00200RW	5.0	1.0	36	200	coil
0295133	5x2x0.5	1003543-01000DO	6.0	1.0	50	1000	K6
0255133	5x2x0.5	1003543-00150RW	6.0	1.0	50	150	coil
0255134	10x2x0.5	1003614-01000DX	7.6	1.0	78	1000	K6
0255135	10x2x0.5	1003614-00200RS	7.6	1.0	78	200	coil
0255136	20x2x0.5	1003615	9.5	1.0	130	1000	K7
0255137	30x2x0.5	1003616	11.5	1.1	185	1000	K8
0255138	50x2x0.5	1003617	14.0	1.1	285	1000	K9
0255140	100x2x0.5	1003559	19.0	1.2	550	1000	K12
0255142	200x2x0.5	1004739	26.0	1.5	1030	1000	K16